

Flashing an Object White with Params

(Using a shader that accepts parameters)

Useful for indicating hits on an object, for example in shoot-em-ups.

Assets



Code

```
orxObject_CreateFromConfig("Object");
```

Config

```
[Object]
Graphic          = Graphic
ShaderList      = WhiteShader

[Graphic]
Texture         = ship.png

[WhiteShader]
ParamList       = texture # objectTime # flashSpeed # maxFlashes
objectTime     = time
maxFlashes     = 4 ;how many times to flash
flashSpeed     = 8 ;how fast between flashes
Code           = "
void main() {

    vec2 p = gl_TexCoord[0].xy;
    vec4 textureCol = texture2D(texture, p);

    float t = mod(objectTime*flashSpeed, 1);
    float flashCount = abs(objectTime*flashSpeed);

    if (t < 0.5 && flashCount < maxFlashes){
        gl_FragColor.r = 1.0;
        gl_FragColor.g = 1.0;
```

```
        gl_FragColor.b = 1.0;
        gl_FragColor.a = textureCol.a;
    } else {
        gl_FragColor.rgb = textureCol.rgb;
        gl_FragColor.a = textureCol.a;
    }
}"
```

Result



From: <https://www.orx-project.org/wiki/> - **Orx Learning**

Permanent link: https://www.orx-project.org/wiki/en/examples/shaders/flashing_an_object_white_shader_params

Last update: **2025/09/30 17:26 (8 months ago)**

