# orxSHADER structure

## **Summary**

```
[ShaderTemplate]
Code = "// Shader code
  void main()
  {
  // Do stuff
 }"
KeepInCache
              = <bool>
ParamList
              = ParamFloat # ParamTexture # ParamVector
ParamFloat
              = <float>
ParamVector
               = <vector>
ParamTexture
              = path/to/TextureFile|screen
UseCustomParam = <bool>
```

### **Details**

Here's a list of the available properties for an orxSHADER structure:

- Code: This block 1) contains the code that will be executed. It needs to be provided and be valid GLSL fragment shader code.
- KeepInCache: Defines if the shader code should be kept in memory even if no shader of this type is currently in use. This saves time (reading from disk + compiling) but costs memory. Its default value is false.
- ParamList: This defines the list of parameters needed and used by the shader's code. Every defined parameter must have a default value that will help orx guess their type. If none is provided, then its type will be assumed to be a texture. Available types are <float>, <vector> and texture (if a path to a texture file or the keyword screen is provided). If an invalid path is provided for a parameter, or the parameter isn't defined at all, the owner's texture will be used <sup>2)</sup>. If an explicit list is provided for any parameter, the shader variable will be an array of this parameter type (instead of a regular variable) and its size will be the number of items in the list.
- UseCustomParam: Defines if parameters can have their value overridden at runtime (ie. interactive). Its default value is false which means only the default values will be used.

Here's a simple example of a non-interactive shader as seen in the spawner/shader tutorial.

```
[Decompose]
Code = "void main()
{
  float fRed, fGreen, fBlue;

  // Computes positions with offsets
  vec2 vRedPos = vec2(gl_TexCoord[0].x + offset.x, gl_TexCoord[0].y +
  offset.y);
  vec2 vGreenPos = vec2(gl_TexCoord[0].x, gl_TexCoord[0].y);
```

weeks ago)

```
vec2 vBluePos = vec2(gl TexCoord[0].x - offset.x, gl TexCoord[0].y -
offset.y);
       // Red pixel inside texture?
       if((vRedPos.x \ge 0.0) \&\& (vRedPos.x \le 1.0) \&\& (vRedPos.y \ge 0.0) \&\&
(vRedPos.y \le 1.0)
              // Gets its value
              fRed = texture2D(texture, vRedPos).r;
      // Green pixel inside texture?
       if((vGreenPos.x \ge 0.0) \& (vGreenPos.x \le 1.0) \& (vGreenPos.y \ge 0.0) \& \& (vGreenPos.y \ge 0.0) \& \& (vGreenPos.y \ge 0.0) & \& (vGre
(vGreenPos.y <= 1.0))
       {
              // Gets its value
              fGreen = texture2D(texture, vGreenPos).g;
       }
      // Blue pixel inside texture?
       if((vBluePos.x \ge 0.0) \&\& (vBluePos.x \le 1.0) \&\& (vBluePos.y \ge 0.0) \&\&
(vBluePos.y <= 1.0))
       {
              // Gets its value
              fBlue = texture2D(texture, vBluePos).b;
       }
      // Outputs the final decomposed pixel
       gl_FragColor = vec4(fRed, fGreen, fBlue, 1.0);
ParamList = texture # offset
                                = (-0.05, -0.05, 0.0) \sim (0.05, 0.05, 0.0); \le Let's take some
random offset
```

Please see the spawner/shader tutorial for more information.

#### Overriding Parameters at Runtime with UseCustomParam

Shader parameters can be defined on the fly if

```
UseCustomParam = true
```

is set in your shader. An event of type orxEVENT\_TYPE\_SHADER and ID orxSHADER\_EVENT\_SET\_PARAM will be fired for all parameters and its payload will contain the name of the param and its default value. Event handler can then modify that value if need be, and it'll get used by the shader.

However, when UseCustomParam is defined, those objects can't be batched at rendering. So it might be a bit more expensive. The severity of the processing penalty depends on how many objects are in the scene. See test playgroung code, orxBounce, for an example on how to set those shader parameters on the fly.

#### **Shader Execution Environment**

## **Specifying an Empty Texture**

There is an internal texture called pixel. It can be used to specify an image of arbitrary size when used with the Scale key of the object:

```
[Object]
Graphic = MyTexture
Scale = (16, 16, 1)

[MyTexture]
Texture = pixel
```

In the example above an empty 16×16 pixels texture is created.

This technique can be useful in some types of shaders.

## **Coordinate System**

Shader receives original owner's texture coordinates. For example:

```
[GameObject]
Graphic = @
Texture = ObjectTexture.png
TextureCorner = (16, 16, 0)
TextureSize = (8, 8, 0)
ShaderList = Shader

[Shader]
ParamList = myTexture # ...
Code = ...
```

Then orx will generate extra parameters behind the scene for the texture. The names follow the pattern:

```
<NameOfYourTexture>_top, <NameOfYourTexture>_right,
<NameOfYourTexture>_bottom, <NameOfYourTexture>_left
```

In the example above the names will be:

```
myTexture_top, myTexture_right, myTexture_bottom, myTexture_left
```

Last update:

 $2025/09/30\ en: or x: config: settings\_structure: or x shader \ https://www.or x-project.org/wiki/en/or x/config/settings\_structure/or x shader? rev=1367540049\\ 17:26\ (8$ 

weeks ago)

Let's say myTexture is 32×32, we'd then get:

```
myTexture_left = 16 out of 32 \Rightarrow 0.5

myTexture_top = 32 - 16 out of 32 \Rightarrow 0.5

myTexture_right = 16 + 8 out of 32 \Rightarrow 0.75

myTexture_bottom = 32 - (16 + 8) out of 32 \Rightarrow 0.25 (it has been inverted for you as you can see, same for _top, but in this example it doesn't show)
```

1)

delimited by double quotes (") as seen in the syntax page

2)

if the owner is a viewport, it will be its associated texture; if it's an object, it's current graphic/animation key's texture will be used

From:

https://www.orx-project.org/wiki/ - Orx Learning

Permanent link:

https://www.orx-project.org/wiki/en/orx/config/settings\_structure/orxshader?rev=1367540049

Last update: 2025/09/30 17:26 (8 weeks ago)

